

-

| SuperCub | e Rectangular | Standard Lic | d 292 x 2 | 255 mm | |
|--|---|--|---|--|--|
| · | 5 | | Logical no: | 6141 | |
| Dimensions | | | | | |
| Shape: External length top: External width top: Height: | Rectangular 292 mm +/- 1 mm 255 mm +/- 1 mm 13,2 mm +/- 1 mm | | | | |
| Closure type | | | | | |
| Closure type: | Peel-Off | | | | |
| Lid type: | Standard | | | | |
| Decoration | | | | | |
| Decoration available: | IML | | | | |
| Decoration area offset: | NA mm | | | | |
| Raw material | | | | | |
| Raw material options: | PP | | | | |
| Masterbatch colours: | Colours according to R | PC Superfos standard selec | ted pantone colours | s. | |
| Hot filling: | Notably, plastic packag must be taken in relation to stacking i | The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures | | | |
| Cold temperatures: | The RPC Superfos pac | Freezing conditions require special resins available on request. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures | | | |
| Weight | | | | | |
| Weight: | 105 g +/- 3 g | | | | |
| Packing | | | | | |
| On pallet 1200x800: | 1344 pcs. | On pallet 1200x1000 | 1568 pcs. | | |
| Number per layer: | 12 pcs. | Number per layer: | 14 pcs. | | |
| Height incl. pallet: Stackability, empty: | 0,9 m 5 pallets high | Height incl. pallet: Stackability, empty: | 0,9 m 5 pallets high | | |
| Quality Specifications | 5 pallets high | Stackability, empty. | 5 pallets flight | | |
| Approvals: | 10/2011/EC amendme unless otherwise state ensure that the supplie | d. In accordance with EU lead ad product is sutable for the | d articles intended to gislation, it is the re- intended use. | o come into contact with food sponsibility of the customer to | |
| Shelf life: | months after the date of e.g. direct sun light, | The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per | | | |
| Quality information: | 100,000) are considere | | and therefore cann | not be construed as a defect. | |
| Other UN approval: | No | | | | |
| υν αμμιυναι. | No | | | | |
| Special: | | | | | |
| Specifications are subject to chang notice | e without V | ersion 10.1 | - | Latest revision : 30-09-2012 | |

notice.