

Tork Aftørringspapir Basic 1-lag

Farve: Gul Type: Rulle



Fordel

• Godkendt til kontakt med fødevarer







Produktspecifikation

Artikel	System	Rullelængde	Rullediameter	Indvendig kernediameter	Lag	Farve
127103	W1 - Aftørringspapir væg-/gulv- /standardsystem	1190 m	38 cm	7.1 cm	1	Gul

Beskrivelse

Et 1-lags papir til basale aftørringsopgaver.



Forsendelsesdata

Forbrugerenhed

EAN	7322540069648	
Stk.	1	
Højde	235 mm	
Bredde	380 mm	
Længde	380 mm	
Volumen	33.9 dm3	
Nettovægt	7131 g	
Bruttovægt	7200 g	

Transportenhed

EAN	7310791057132	
Stk.	2	
Forbrugerenhede r	2	
Materiale	Plastic	
Højde	235 mm	
Bredde	380 mm	
Længde	760 mm	
Volumen	67.9 dm3	
Nettovægt	14.26 kg	
Bruttovægt	14.47 kg	

Palle

EAN	7322540176759	
Stk.	42	
Forbrugerenhede r	42	
Højde	1795 mm	
Bredde	800 mm	
Længde	1200 mm	
Volumen	1.4 m3	
Nettovægt	299.50 kg	
Bruttovægt	303.87 kg	



Miljø

Content

Recycled fibres, Chemicals

Material

Recycled fibres Recovered paper can be produced both from collected newsprint, magazines and office waste. The paper is washed with water and treated with chemicals under high temperature and then filtered. Different fibres demand different processes and this determines the end product properties, and makes the fibre type (recovered or virgin) less important. The environmental benefits and economic feasibility of recovered paper as a raw material source depend on its availability, transport distance and the quality of the collected material.

Bleaching of fibres

Bleaching is a cleaning process of the fibres and the aim is to achieve a bright pulp, but also to get a certain purity of the fibre in order to achieve the demands for hygiene products and in some cases to meet the requirements for food safety. There are different methods used today for bleaching ECF (elementary chlorine free(where chlorine dioxide is used, and TCF (totally chlorine free) where ozone, oxygen and hydrogen peroxide is used.

Chemicals

The chemicals used in the process as well as the functional chemicals are assessed from an environmental, occupational health and safety and product safety point of view. The used functional chemicals are: Wet strangth agentDry strength agent If coloured = Dye Fixing agents Fluorescent whitening agent Glue Softeners The process chemicals are: Antipitch Protection agent Yankee coating Defoamer Dispersing agents and surfactants pH and charge control Retention aids Broke treatment chemicals Drainage aid

Product safety

The product fulfils the legislative requirements for food safety =Isega. Packaging Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes Environmental label Approved and labeled according to Swan. License no. 305003.

Date of issue 2007-08-27

Revision date 2009-11-02



Production

This product is produced in Lilla Edet mill, Sweden, certified according to ISO 9001, ISO 14001.

Destruction

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destructed. The product itself is suitable for incineration. Contact local authorities before destruction.

