

DATASHEET

QuickFix Elastic

1. Identification of the substances/preparation and of the company/undertaking

Date issued	11.10.2004
Revision	06.04.2006
Product name	Quick Fix Elastic
Index no.	Version 1.1
Use of the substance/preparation	Plaster QuickFix Elastic

Producer

Company name	Plum A/S
Postal address	Frederik Plums Vej 2
Postcode	5610
Place name	Assens
Country	Danmark
Tel.	0045 6471 2112
Fax	0045 6471 21 25
E-mail	info@plum.dk
Website	http://www.plum.dk

2. Backing

Composition	CD elastic fabric (65% cotton, 35% polyamide)
Colour	Pink
Weight (g/m ²)	80-100
MD Tensile strenght (N/cm)	>30

3. Adhesive

Composition	Hypoallergenic acrylic polymer
Weight (g/m ²)	55-65

4. Coated backing

Weight (g/m ²)	135-165
Adhesion to steel by peeling at 180° (N/cm)	>1,2
M.V.T.R. (g/m ² /24h/37°C)	>500
Water resistant	no

5. Absorbent pad

Total weight (g/m ²)	100-160
Absorbency (g/100 cm ²)	9-16
Absorbent layer	Viscose and polypropylene nonwoven
Colour	White
Antiadherent layer	Microperforated PE film

6. Liner

Monosiliconated paper

Weight (g/m ²)	57-63
Colour	White

QuickFix Elastic

7. Primary packing

Individual pouch: paper + clear film

Paper composition	Cold sealed paper
Paper weight (g/m ²)	40-50
Film composition	Polyethylene terephthalate / polyethylene
Film weight (g/m2)	52-67